



CN



易得科技  
AUTOEDE



# GT系列

## 技术资料

### PP / PET 锂电自动打包机



更友善的参数可视界面显示：  
(张紧力, 做扣时长, 剩余电量)

做扣启动按钮

收带张紧按键

业界一流的人机工程  
学设计防滑手柄

盖板易于拆卸  
方便维护

“软”打包模式  
适用于易损表面



# GT系列

## 技术资料



易得科技  
AUTOEDE



型号 订货号	GT-Smart* #C159990812Z	GT-ONE* #C155880812Z	GT-Xtreme #C160990812Z	GT-MAX #C164990812Z
工作模式	手动	自动 / 手动 / 半自动	自动 / 手动 / 半自动	自动 / 手动 / 半自动
张紧力	标准 软模式 650 – 1.800 N 240 – 1.000 N	1.200 – 2.800 N 500 – 1.500 N	2.200 – 4.200 N 1.100 – 3.100 N	2.500 – 6.500 N 1.800 – 5.000 N
最大收带速度	14 m/min	12 m/min	9 m/min	5 m/min
做扣强度	75 – 85 %	75 – 85 %	75 – 85 %	75 – 85 %
整机重量 (包含电池)	3,75 kg	3,75 kg	4,0 kg	6,2 kg
外形尺寸 (L x W x H)	330 x 105 x 160 mm	330 x 105 x 160 mm	330 x 105 x 160 mm	425 x 135 x 180 mm
工作环境温度	-5°C - 40°C	-5°C - 40°C	-5°C - 40°C	-5°C - 40°C
工作环境湿度	20 – 90 %	20 – 90 %	20 – 90 %	20 – 90 %
最大噪音 (做扣焊接时)	≈96 dB(A)	≈96 dB(A)	≈96 dB(A)	≈113 dB(A)
<b>电池 / 充电器</b>				
充电器品牌	Akku-Power	Akku-Power	Akku-Power	Akku-Power
供电电压	230 V	230 V	230 V	230 V
一次充满时长	≈ 40 min	≈ 50 min	≈ 30 min	≈ 45 min
电池容量	Akku Power Li-Ion 14,4 V, 3.0 Ah	Akku Power Li-Ion 14,4 V, 4.0 Ah	Akku Power Li-Ion 18 V, 5.0 Ah	Akku Power Li-Ion 36 V, 5.0 Ah
每充一次可打包次数	150 – 200	150 – 350	180 – 300	150 – 300
<b>捆带参数</b>				
类型	PP / PET	PP / PET	PP / PET	PET
宽度 (mm)	9 – 10 – 13 – 16	10 – 13 – 16	16 – 19	25 – 32
厚度 (mm)	0,4 – 0,85	0,5 – 1,1	0,8 – 1,27	0,9 – 1,3 mm
<b>优异特征</b>				
轻盈 & 平衡	•	•	•	•
显示锁定	•	•	•	•
“循环结束”提示、声音	•	•	•	•
自动断电	•	•	•	•
顺滑的提拉手柄	•	•	•	•
不锈钢材质	-	-	•	-
打包循环次数显示	•	•	•	•

### 可选附件

- 额外的电池 & 充电器
- 手提箱
- 挂钩 [A]
- 金属保护盖板 [B]
- 底板 [C]
- 电源直供线 (无电池情况下使用) [D]

